



(19)

Europäisches Patentamt

European Patent Office

Office européen des brevets



(11)

EP 1 293 270 A2

(12)

EUROPEAN PATENT APPLICATION

(43) Date of publication:

19.03.2003 Bulletin 2003/12

(51) Int Cl.7: B21D 26/02

(21) Application number: 02255346.5

(22) Date of filing: 31.07.2002

(84) Designated Contracting States:

AT BE BG CH CY CZ DE DK EE ES FI FR GB GR
IE IT LI LU MC NL PT SE SK TR

Designated Extension States:

AL LT LV MK RO SI

(30) Priority: 27.08.2001 US 940106

(71) Applicant: ArvinMeritor Technology, LLC
Troy, Michigan 48084 (US)

(72) Inventor: Doplico Varela, Tomaz

Gahanna, Ohio 43230 (US)

(74) Representative: Jones, John Bryn et al

Withers & Rogers,

Goldings House,


2 Hays Lane

London SE1 2HW (GB)

(54) Axle assembly and a method of forming an axle

(57) An axle assembly is provided that includes a tubular member having an outer wall and an interior cavity. The outer wall includes a first interlocking feature. An axle component mounting member, such as a bearing shoulder sleeve and/or a brake flange, is arranged on a portion of the outer wall. The mounting member includes a second interlocking feature coacting with the first interlocking feature to affix the mounting member

and tubular member to one another. The axle assembly may be formed by arranging the axle mounting member into a die assembly. A tubular member may be arranged in the die assembly within an opening in the mounting member. A hydroforming process may be employed to pressurize a cavity within the tubular member. A portion of the tubular member is deformed into engagement with the mounting member to affix the mounting member to the tubular member.

Fig-1

Description

BACKGROUND OF THE INVENTION

[0001] This invention relates to an axle assembly, and more particularly, the invention relates to a hydroformed axle with a bearing shoulder and brake flange that are secured thereto preferably without the use of welds.

[0002] Many prior art axle assemblies, such as for use in trucks or trailers, are constructed from tubes or solid members that are straight or bent to a desired shape. Numerous components are typically secured to the axle, typically by welding the axle component to the axle. For example, the brake assembly is supported on the axle by a brake flange, which is welded to the axle. Welding components to the axle requires that a consumable welding material be deposited on the brake component axle in a relatively precise manner. As a result, the welding process may be expensive and difficult to control.

[0003] The wheels are supported on the ends of the axle on bearing assemblies. Bearing races are pressed onto the axle to abut a shoulder, which may be machined onto the axle, to locate the bearings axially. Machining can be a relatively expensive process therefore, what is needed is an axle assembly on which a bearing shoulder may be provided and to which a brake flange may be secured to without the use of expensive machining or welding.

SUMMARY OF THE INVENTION AND ADVANTAGES

[0004] The present invention provides an axle assembly including a tubular member having an outer wall and an interior cavity. The outer wall includes a first interlocking feature. An axle component mounting member, such as a bearing shoulder sleeve and/or a brake flange, is arranged on a portion of the outer wall. The mounting member includes a second interlocking feature coacting with the first interlocking feature to affix the mounting member and tubular member to one another. The axle assembly may be formed by arranging the axle mounting member into a die assembly. A tubular member may be arranged in the die assembly within an opening in the mounting member. A hydroforming process may be employed to pressurize a cavity within the tubular member. A portion of the tubular member is deformed into engagement with the mounting member to affix the mounting member to the tubular member.

[0005] Accordingly, the above invention provides an axle assembly on which a bearing shoulder may be provided and to which a brake flange may be secured to without the use of expensive machining or welding.

BRIEF DESCRIPTION OF THE DRAWINGS

[0006] Other advantages of the present invention can be understood by reference to the following detailed description when considered in connection with the ac-

companying drawings wherein:

Figure 1 is a cross sectional view of a tubular member and axle component mounting member within a die assembly forming the axle assembly of the present invention;

Figure 2 is an enlarged view of the axle assembly of the present invention subsequent to forming;

Figure 3 is a side elevational view of a bearing shoulder sleeve and brake flange secured to the tubular member by the present invention axle forming process;

Figure 4 is a cross-sectional view of the bearing shoulder sleeve taken along lines 4-4 of Figure 3;

Figure 5A is a partial cross-sectional view of one embodiment of the interlocking features taken along line 5-5 of Figure 3; and

Figure 5B is a partial cross-sectional view of another embodiment of the interlocking features taken along line 5-5 of Figure 3.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

[0007] The die assembly 10 is shown in Figures 1 and 2 and includes first 12 and second 14 die portions. Together the die portions 12 and 14 provide a forming surface 15 that defines the shape of the axle assembly to be formed. The die portions 12 and 14 include mounting member receptacles 18 and 20 within the forming cavity 16 of the die assembly 10. A bearing shoulder sleeve 22 may be arranged in one of the receptacles 18, and a brake flange 24 may be arranged in the other receptacle 20. The bearing shoulder sleeve 22 provides a shoulder against which bearing assemblies may be installed. The brake flange 24 provides a mount to which a brake assembly for the wheel may be secured.

[0008] The bearing shoulder sleeve 22 and brake flange 24 respectively include openings 23 and 25. A tubular member 26 is inserted into the forming cavity 16 and is arranged within the openings 23 and 25. The tubular member 26 includes an outer wall 28 and an interior cavity 30. Utilizing a known hydroforming process, the cavity 30 is pressurized with the hydraulic fluid to force the outer wall 28 into engagement with the forming surface 15 of the die portions 12 and 14. The outer wall 28 is deformed such that it engages the openings 23 and 25. Preferably, the openings 23 and 25 of the mounting members include a generally concaved annular surface such that the deformed outer wall 28 of the tubular member 26 locates the mounting members 22 and 24 axially on the tubular member 26.

[0009] The tubular member 26 and mounting members 22 and 24 may respectively include first 36 and second 38 interlocking features. For example, the interlocking features may be complementary and recesses or splines, as shown in Figure 5A. Alternatively, the mounting member may include a hole 40 that receives a pro-

trusion 42 formed during the hydroforming process. The interlocking features 36 and 38 ensure that the mounting members 22 and 24 do not move axially or rotationally relative to the tubular member 26.

[0010] Referring to Figure 4, a material 34 such as a polymeric film or adhesive may be arranged between the mounting members 22 and 24 and the tubular member 26 to prevent corrosion. The material 34 may be selected such that a seal is created between the bearing shoulder sleeve 22 and the tubular member 26 to prevent leakage of lubricant past the bearing shoulder sleeve 22.

[0011] In this manner, a shoulder for the bearing assembly may be provided without machining the axle. Moreover, the brake flange 24 may be secured to the axle without welding. Post heat treatment of the axle assembly may not be necessary with the present invention hydroforming process.

[0012] The invention has been described in an illustrative manner, and it is to be understood that the terminology that has been used is intended to be in the nature of words of description rather than of limitation. Obviously, many modifications and variations of the present invention are possible in light of the above teachings. It is, therefore, to be understood that within the scope of the appended claims the invention may be practiced otherwise than as specifically described.

Claims

1. A method of forming an axle (26 of figure 2) comprising the steps of:
 - a) arranging an axle component mounting member (22, 24) into a die assembly (10);
 - b) arranging a tubular member (26 of figure 1) in the die assembly within an opening in the mounting member;
 - c) pressurizing a cavity (30) within the tubular member; and
 - d) deforming a portion the tubular member into engagement with mounting member to affix the mounting member to the tubular member.
2. The method according to claim 1, further including the step of arranging a material (34) between the mounting component and the tubular member for preventing corrosion therebetween.
3. The method according to claim 1 or 2, wherein the mounting member includes a recess, and step d) includes deforming a portion of the tubular member into the recess.
4. The method according to claim 3, wherein the recess is at least one hole (40).
5. The method according to claim 3, wherein the recess is defined by a splined surface (36, 38) arranged about the tubular member.
6. The method according to any preceding claim, further including the step of hydroforming the tubular member into a desired axle shape.
7. The method according to any preceding claim, wherein the opening of the mounting member is defined by a generally concave surface.
8. An axle assembly comprising:
 - a tubular member having an outer wall and an interior cavity, said outer wall including a first interlocking feature; and
 - an axle component mounting member arranged on a portion of said outer wall, said mounting member including a second interlocking feature coacting with said first interlocking feature to affix said mounting member and tubular member to one another.
9. The assembly according to claim 8, further including a material disposed between said portion of said outer wall and mounting member.
10. The assembly according to claim 8 or 9, wherein said interlocking features include complimentary splines.
11. The assembly according to claim 8 or 9 or 10, wherein said second interlocking feature is a hole and said first interlocking feature is a protrusion extending into said hole.
12. The assembly according to claim 8 or 9 or 10 or 11, wherein said mounting member includes a generally concave annular surface in engagement with said portion of said tubular member.
13. The method or assembly according to any preceding claim, wherein the mounting member is a bearing shoulder sleeve (22).
14. The method or assembly according to any one of claims 1 to 12, wherein the mounting member is a brake flange (24).




Fig-1








Fig-2





(11) **EP 1 293 270 A3**

(12) **EUROPEAN PATENT APPLICATION**

(88) Date of publication A3:
05.11.2003 Bulletin 2003/45

(51) Int Cl.7: **B21D 26/02**

(43) Date of publication A2:
19.03.2003 Bulletin 2003/12

(21) Application number: 02255346.5

(22) Date of filing: 31.07.2002

(84) Designated Contracting States:
**AT BE BG CH CY CZ DE DK EE ES FI FR GB GR
 IE IT LI LU MC NL PT SE SK TR**
 Designated Extension States:
AL LT LV MK RO SI

(72) Inventor: **Dopico Varela, Tomaz**
Gahanna, Ohio 43230 (US)

**(74) Representative: Jones, John Bryn et al
Withers & Rogers,
Goldings House,
2 Hays Lane
London SE1 2HW (GB)**

(30) Priority: 27.08.2001 US 940106

(71) Applicant: **ArvinMeritor Technology, LLC**
Troy, Michigan 48084 (US)

(54) **Axle assembly and a method of forming an axle**

(57) An axle assembly is provided that includes a tubular member having an outer wall and an interior cavity. The outer wall includes a first interlocking feature. An axle component mounting member, such as a bearing shoulder sleeve and/or a brake flange, is arranged on a portion of the outer wall. The mounting member includes a second interlocking feature coacting with the first interlocking feature to affix the mounting member

and tubular member to one anther. The axle assembly may be formed by arranging the axle mounting member into a die assembly. A tubular member may be arranged in the die assembly within an opening in the mounting member. A hydroforming process may be employed to pressurize a cavity within the tubular member. A portion of the tubular member is deformed into engagement with the mounting member to affix the mounting member to the tubular member.




Fig-1



European Patent
Office

EUROPEAN SEARCH REPORT

Application Number
EP 02 25 5346

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.7)
X	US 5 280 672 A (HOCHSTEIN PETER A) 25 January 1994 (1994-01-25) * column 5, line 30 - line 64; figure 8 *	1,3-6,8, 10,11,13	B21D26/02
Y	---	2,7,9,12	
Y	US 5 447 385 A (SWARS HELMUT) 5 September 1995 (1995-09-05) * column 3, line 26 - line 35 *	2,9	
Y	US 5 101 554 A (BREUER HANS-JUERGEN ET AL) 7 April 1992 (1992-04-07) * figure 2D *	7,12	
X	PATENT ABSTRACTS OF JAPAN vol. 010, no. 331 (M-533), 11 November 1986 (1986-11-11) & JP 61 135434 A (NISSAN MOTOR CO LTD), 23 June 1986 (1986-06-23) * abstract *	1-4,6,8, 9,11,13	
			TECHNICAL FIELDS SEARCHED (Int.Cl.7)
			B21D
The present search report has been drawn up for all claims			
Place of search THE HAGUE		Date of completion of the search 12 September 2003	Examiner Gerard, O
<p>CATEGORY OF CITED DOCUMENTS</p> <p>X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document</p> <p>T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document</p>			

EPO FORM 1303 03/02 (P04C01)

BEST AVAILABLE COPY

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 02 25 5346

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report.
The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

12-09-2003

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 5280672 A	25-01-1994	US 5220727 A	22-06-1993
		CA 2099082 A1	26-12-1993
		EP 0592068 A1	13-04-1994
US 5447385 A	05-09-1995	DE 3742480 A1	29-06-1989
		US 5287615 A	22-02-1994
		BR 8806589 A	22-08-1989
		CA 1325883 C	11-01-1994
		DE 3871105 D1	17-06-1992
		EP 0320789 A2	21-06-1989
		IN 170925 A1	13-06-1992
		JP 1197022 A	08-08-1989
		KR 9306043 B1	03-07-1993
		MX 172866 B	18-01-1994
US 5101554 A	07-04-1992	DE 3633435 A1	14-04-1988
		BR 8705053 A	24-05-1988
		CA 1294798 C	28-01-1992
		CN 87106724 A ,B	20-04-1988
		DE 3788191 D1	23-12-1993
		EP 0265663 A1	04-05-1988
		ES 2046190 T3	01-02-1994
		IN 167866 A1	29-12-1990
		JP 1779031 C	13-08-1993
		JP 4065729 B	21-10-1992
		JP 63119937 A	24-05-1988
		MX 173130 B	02-02-1994
		SU 1722243 A3	23-03-1992
JP 61135434 A	23-06-1986	NONE	

EPO FORM P0459

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82

BEST AVAILABLE COPY